

Rock Mineral Wool - High Temperature Products

Product name:	Rock Mineral Wool - High Temperature Products	Page:	1/11
Revision Date:	2015-06-15	Print date:	2015-06-16
Product No.:	KI_DP_202	SDS-ID:	ITe-EN/2.0

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Knauf Insulation Rock mineral wool.

Product name: Rock Mineral Wool - High Temperature Products

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified use(s): Thermal and/or acoustic insulation for use in technical applications, industrial applications and in building construction.

1.3. Details of the supplier of the safety data sheet

Head Office Knauf Insulation
Am Bahnhof
97346 Iphofen
Germany
Tel:+32 (0) 1048 8460
sds@knaufinsulation.com
www.knaufinsulation.com

Country Contact: Italy
Tel:+39 (0) 119 119 6214
mariateresa.favola@knaufinsulation.com

1.4. Emergency telephone number

SECTION 2: HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture


GHS/CLP CE N°1272/2008 The product is not classified.

2.2. Label elements

The product is not classified.

The following sentences and pictograms are printed on packaging:

The mechanical effect of fibres in contact with skin may cause temporary itching.



<http://www.knaufinsulation.com/comfort-and-handling>

2.3. Other hazards

Specific hazards: For product with binder: When heated to temperatures above 200°C for the first time, release of binder components and binder decomposition products can occur which, in high concentrations, may irritate eyes and the respiratory system.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.2. Mixtures

GHS/CLP CE N° 1272/2008

<u>%:</u>	<u>CAS-No.:</u>	<u>EC No.:</u>	<u>REACH Reg. No.:</u>	<u>Chemical name:</u>	<u>Hazard classification:</u>	<u>Notes:</u>
90 - 100 -		926-099-9	01-2119472313-	Rock Mineral Wool	-	
0 - 10 -		-	-	Thermo set, inert polymer based on cured phenol formaldehyde resin	-	

Notes: (1) Man made vitreous (silicate) fibres with random orientation with alkaline oxide and alkali earth oxide (Na₂O+K₂O+CaO+MgO+BaO) content greater than 18% by weight meeting the requirements of Note Q of regulation n° 1272/2008 and therefore not classified carcinogenicity.
(2) CAS-No.: Chemical Abstract Service

Possible facing materials: glass veil, or polyester mat or aluminium or Kraft paper, wired mats.

SECTION 4: FIRST AID MEASURES

4.1. Description of first aid measures

<u>Inhalation:</u>	Remove from exposure. Rinse the throat and clear dust from airways.
<u>Skin contact:</u>	If mechanical irritation occurs, remove contaminated clothing and wash skin gently with cold water and soap.
<u>Eye contact:</u>	Rinse abundantly with water for at least 15 minutes.
<u>Ingestion:</u>	Drink plenty of water if accidentally ingested.

4.2. Most important symptoms and effects, both acute and delayed

The mechanical effect of fibres in contact with skin may cause temporary itching.

4.3. Indication of any immediate medical attention and special treatment needed

If any adverse reaction or discomfort continues from any of the above exposures, seek professional medical advice.

Product name:	Rock Mineral Wool - High Temperature Products	Page:	4/11
Revision Date:	2015-06-15	Print date:	2015-06-16
Product No.:	KI_DP_202	SDS-ID:	ITe-EN/2.0

SECTION 5: FIREFIGHTING MEASURES

5.1. Extinguishing media

Extinguishing media: Water, foam, carbon dioxide (CO₂), and dry powder.

5.2. Special hazards arising from the substance or mixture

Products do not pose a fire hazard in use; however, some packaging materials or facings may be combustible. Products of combustion from product and packaging - carbon dioxide, carbon monoxide and some trace gases such as ammonia, nitrogen oxides and volatile organic substances.

5.3. Advice for firefighters

In large fires in poorly ventilated areas involving packaging materials respiratory protection / breathing apparatus may be required.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: In case of presence of high concentrations of dust, use the same personal protective equipment as mentioned in section 8.

6.2. Environmental precautions

Environmental precautions: Not relevant.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up: Vacuum cleaner or dampen down with water spray prior to brushing up.

6.4. Reference to other sections

For personal protection, see section 8. For waste disposal, see section 13.

Product name: Rock Mineral Wool - High Temperature Products Page: 5/11
Revision Date: 2015-06-15 Print date: 2015-06-16
Product No.: KI_DP_202 SDS-ID: ITe-EN/2.0

SECTION 7: HANDLING AND STORAGE

7.1. Precautions for safe handling

Safe handling advice: Avoid unnecessary handling of unwrapped product.
Technical measures: No specific measures. Cut using a knife, do not use a saw or use power tools.
Technical precautions: Provide adequate ventilation.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions:
To ensure optimum product performance; when packaging is removed or opened; products should be stored inside or covered to protect them from ingress of rain water or snow.
Storage arrangements should ensure stability of stacked products and use on a first in first out basis (FIFO) is recommended.

No incompatible groups noted.

Delivered packed in polyethylene film and or on wooden pallets.

7.3. Specific end use(s)

Specific use(s): Not relevant.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure limits: None at European level, refer to member state guidelines and legislation:

8.1. Control parameters

Occupational exposure limits:

<u>CAS-No.:</u>	<u>Chemical name:</u>	<u>As:</u>	<u>Exposure limits:</u>	<u>Type:</u>	<u>Notes:</u>	<u>References:</u>
-	Rock wool fibers	-	1 fiber/ml	TWA	A3	ACGIH

8.2. Exposure controls

Engineering measures: No specific measures.
Respiratory equipment: Wearing a face mask type in accordance with EN 149 FFP1 is recommended when using products in confined atmosphere or during operations which can generate emission of any dust.
Hand protection: Use gloves to avoid itching in conformity with EN 388.
Eye protection: Use goggles especially if working above shoulders. Eye protection according to EN 166 is advised.
Skin protection: Cover exposed skin.
Hygiene measures: After contact, wash hands with cold water and soap.

Product name:	Rock Mineral Wool - High Temperature Products	Page:	6/11
Revision Date:	2015-06-15	Print date:	2015-06-16
Product No.:	KI_DP_202	SDS-ID:	ITe-EN/2.0

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

<u>Appearance:</u>	Solid.
<u>Form:</u>	Roll or panel.
<u>Colour:</u>	Ochre.
<u>Odour:</u>	Not relevant.
<u>pH:</u>	Not relevant.
<u>Boiling point:</u>	Not relevant.
<u>Flash point:</u>	Not relevant.
<u>Flammability (solid, gas):</u>	Not relevant.
<u>Explosion limits:</u>	Not relevant.
<u>Relative density:</u>	30 - 250 kg/m ³
<u>Solubility:</u>	Generally chemically inert and insoluble in water.

9.2. Other information

Fibre melting point: > 1000 °C according to DIN 4102-17. Approved. = <700°C

Nominal diameter of fibres. 3 - 7 µm

Length weight geometric mean diameter less 2 standard errors: ≈ 6 µm

Orientation of fibres: Random.

Product name:	Rock Mineral Wool - High Temperature Products	Page:	7/11
Revision Date:	2015-06-15	Print date:	2015-06-16
Product No.:	KI_DP_202	SDS-ID:	ITe-EN/2.0

SECTION 10: STABILITY AND REACTIVITY

10.1. Reactivity

Reactivity: None.

10.2. Chemical stability

Stability: None.

10.3. Possibility of hazardous reactions

Hazardous Reactions: None in normal conditions of use.

10.4. Conditions to avoid

Conditions/materials to avoid:
None.

10.5. Incompatible materials

Incompatible materials: None.

10.6. Hazardous decomposition products

Hazardous decomposition products: For product with binder: When heated to temperatures above 200°C for the first time, release of binder components and binder decomposition products can occur which, in high concentrations, may irritate eyes and the respiratory system.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information on toxicological effects

The mechanical effect of fibres in contact with skin may cause temporary itching.

Classification not applicable for this product; in accordance with European Regulation 1272/2008, note Q.

Product name:	Rock Mineral Wool - High Temperature Products	Page:	8/11
Revision Date:	2015-06-15	Print date:	2015-06-16
Product No.:	KI_DP_202	SDS-ID:	ITe-EN/2.0

SECTION 12: ECOLOGICAL INFORMATION

12.1. Toxicity

Ecotoxicity: This product is not ecotoxic to air, water or soil, by composition.

12.2. Persistence and degradability

Degradability: Inert inorganic product with Thermo set, inert polymer based on cured phenol formaldehyde resins; 0 - 10%

12.3. Bioaccumulative potential

Bioaccumulative potential: Will not bio-accumulate.

12.4. Mobility in soil

Mobility: Not considered mobile. Less than 1% leachable organic carbon if landfilled.

12.5. Results of PBT and vPvB assessment

PBT/vPvB: Not relevant.

12.6. Other adverse effects

Other adverse effects: None known.

SECTION 13: DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Waste from residues: Dispose of in accordance with regulations and procedures in force in country of use or disposal.

Contaminated packaging: Dispose of in accordance with regulations and procedures in force in country of use or disposal.

EWC-code: 17 06 04, Non-hazardous substance.

Product name:	Rock Mineral Wool - High Temperature Products	Page:	9/11
Revision Date:	2015-06-15	Print date:	2015-06-16
Product No.:	KI_DP_202	SDS-ID:	ITe-EN/2.0

SECTION 14: TRANSPORT INFORMATION

The product is not covered by international regulation on the transport of dangerous goods (IMDG, IATA, ADR/RID).

14.1. UN number

UN-No: -

14.2. UN proper shipping name

Proper Shipping Name: -

14.3. Transport hazard class(es)

Class: -

14.4. Packing group

Packing group: -

14.5. Environmental hazards

Marine pollutant: -

Environmentally Hazardous substance: -

14.6. Special precautions for user

Special precautions: None known.

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Transport in bulk: Not relevant.

Product name:	Rock Mineral Wool - High Temperature Products	Page:	10/11
Revision Date:	2015-06-15	Print date:	2015-06-16
Product No.:	KI_DP_202	SDS-ID:	ITe-EN/2.0

SECTION 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

The European Regulation on Chemicals No 1907/2006, Registration, Evaluation, Authorisation of Chemicals (REACH) enacted on June 1st 2007 requires the provision of Safety Data Sheet (SDS) for hazardous substances and mixtures / preparations.

Knauf Insulation mineral wool products (panels, batts or rolls), are defined as articles under REACH and therefore a Safety Data Sheet for these products is not a legal requirement.

In accordance with industry practice and voluntary commitments, Knauf Insulation has decided to continue to provide its customers with the appropriate information for the purpose of assuring safe handling and use of mineral wool throughout the product life.

This material Safety Data Sheet / Product Data Sheet is in accordance with the EU directives 1907/2006, 1272/2008 and 453/2010.

15.2. Chemical Safety Assessment

CSA status: Not relevant.

Product name:	Rock Mineral Wool - High Temperature Products	Page:	11/11
Revision Date:	2015-06-15	Print date:	2015-06-16
Product No.:	KI_DP_202	SDS-ID:	ITe-EN/2.0

SECTION 16: OTHER INFORMATION

All products manufactured by Knauf Insulation are made of non-classified fibres and are certified by EUCEB.

EUCEB, European Certification Board of Mineral Wool Products - www.euceb.org, is a voluntary initiative by the mineral wool industry. It is an independent certification authority that guarantees that products are made of fibres, which comply with the exoneration criteria for carcinogenicity (Note Q) of the Regulation (EC) 1272/2008.

The mineral wool producers commit to EUCEB to:

- supply sampling and analysis reports established by laboratories recognized by EUCEB, proving that the fibres comply with one of the four criteria of exoneration described in Note Q,
- be controlled, twice per year, of each production unit by an independent third party recognized by EUCEB (sampling and conformity to the initial chemical composition),
- put in place procedures of internal self-control in each production unit.

Products meeting EUCEB certification requirements can be recognised by the EUCEB logo printed on the packaging.

Further information can be obtained from:

www.euceb.org

www.knaufinsulation.com



Product Families

: High Temperature Boards, Lamella Mats, Wired Mats, Felt Mats, Pipe Sections, Tank Boards, Marine, HVAC Fire Protection Boards

Additional information:

Change to Sections: 2.1, 2.2, 2.3, 3.2, 4.1, 5.3, 10.4, 11.1, 15.1, 16

Moreover, in 2001, the IARC, reclassified glass mineral wool fibres from Group 2B (possibly carcinogenic) to «not classifiable as to their carcinogenicity to humans (Group 3)». (See Monograph Vol 81, <http://monographs.iarc.fr/>).

The information on this data sheet represents our current data and is reliable provided that the product is used under the prescribed conditions and in accordance with the application specified on the packaging and/or in the technical guidance literature. Any other use of the product which involves using the product in combination with any other product or any other process is the responsibility of the user.
