



SAFETY DATA SHEET

Rock Mineral Wool Insulation Material (Needled Felt)

According to Appendix D, OSHA Hazard Communication Standard 29 CFR §1910.1200

1. Identification

Product identifier

- Knauf Insulation Rock mineral wool.

Product name Rock Mineral Wool Insulation Material (Needled Felt)

Product number KI_DP_504 (GHS)

Synonyms; trade names KI DAP NFSA, KI DAP NFSP, KI DAP NFSH

Revision date: 02/22/2017

Recommended use of the chemical and restrictions on use

Application Thermal insulation for use in industrial applications OEM DAP product.

Uses advised against None known.

Details of the supplier of the safety data sheet

Supplier

Knauf Insulation, Inc.
One Knauf Drive
Shelbyville
IN 46176-1496
oem@knaufinsulation.com
www.oem.knaufinsulation.com
Tel: 800 825 4434

Region: United States, Central & South America

Emergency telephone number

Emergency telephone 24hrs: Chemtrec Tel: 800 424 9300

2. Hazard(s) identification

Classification of the substance or mixture

OSHA Regulatory Status This product is regulated as a nuisance dust under OSHA criteria.

Physical hazards Not Classified

Health hazards Not Classified

Environmental hazards Not Classified

Label elements

Hazard statements NC Not Classified

Contains None.

Hazard pictogram None.

Rock Mineral Wool Insulation Material (Needled Felt)

Signal word None.

Precautionary statements None.

Supplemental label information None.

The following sentences and pictograms are printed on packaging:

The mechanical effect of fibers in contact with skin may cause temporary itching.



<http://www.knaufinsulation.com/comfort-and-handling>

Other hazards

Physical Hazards None.

Health Hazards Mechanical irritation of the skin, eyes and upper respiratory system.

Environmental Hazards None.

Main symptoms Contact with skin, eyes and upper respiratory system may cause mechanical irritation. Biosoluble rock mineral wool is classified as a nuisance dust by OSHA.

3. Composition/information on ingredients

Mixtures

Vitreous silicate fibers produced under process conditions	>99%
---	----------------

CAS number: —

Ingredient notes:(1)(2)

Classification

Not Classified

The full text for all hazard statements is displayed in Section 16.

Ingredient notes

(1) Man made vitreous (silicate) fibers with random orientation with alkaline oxide and alkali earth oxide ($\text{Na}_2\text{O}+\text{K}_2\text{O}+\text{CaO}+\text{MgO}+\text{BaO}$) content greater than 18% by weight meeting the requirements of Note Q of regulation n° 1272/2008 and therefore not classified carcinogenicity.

(2) All Knauf Insulation products covered by this SDS are independently certified by EUCEB to be manufactured using biosoluble rock formulations and thus exempt from labeling under NTP or California Prop 65 requirements.

Specific chemical identity and/or exact percent concentration is withheld as trade secret.

Rock Mineral Wool Insulation Material (Needled Felt)

4. First-aid measures

Description of first aid measures

General information	Show this Safety Data Sheet to the medical professional in attendance. If symptoms occur, follow first aid measures as appropriate.
Notes to Physician:	No specific recommendations.
Inhalation	Remove from exposure. Rinse the throat and clear dust from airways.
Ingestion	Drink plenty of water if accidentally ingested.
Skin Contact	If mechanical irritation occurs, remove contaminated clothing and wash skin gently with cold water and soap.
Eye contact	Rinse abundantly with water for at least 15 minutes.

Most important symptoms and effects, both acute and delayed

General information	Contact with skin, eyes and upper respiratory system may cause mechanical irritation. Biosoluble rock mineral wool is classified as a nuisance dust by OSHA.
----------------------------	--

Indication of immediate medical attention and special treatment needed

General information	If any adverse reaction or discomfort continues from any of the above exposures, seek professional medical advice.
Specific treatments	No specific recommendations.

5. Fire-fighting measures

Extinguishing media

Suitable extinguishing media Water, foam, carbon dioxide (CO₂), and dry powder.

Special hazards arising from the substance or mixture

General information	Products do not pose a fire hazard in use; however, some packaging materials or facings may be combustible. Products of combustion from product and packaging - carbon dioxide, carbon monoxide and some trace gases such as ammonia, nitrogen oxides and volatile organic substances.
----------------------------	--

Advice for firefighters

General information	In large fires in poorly ventilated areas involving packaging materials respiratory protection / breathing apparatus may be required.
----------------------------	---

Rock Mineral Wool Insulation Material (Needled Felt)

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Personal precautions

Minimize direct contact with skin in order to prevent mechanical itching. In dusty environments, use suitable respiratory protection such as 3M 8210, N95 or equivalent. Use glasses or goggles when working with mineral wool insulation above shoulder height or in dusty environments. Where possible, use natural ventilation during installation in order to minimize dust levels.

After contact with the product, rinse skin in cold water to reduce potential effects of mechanical itching. Dispose of surplus product in accordance with local regulations.

Use personal protection recommended in Section 8 of the SDS.

Environmental precautions

Environmental precautions Not relevant.

Methods and material for containment and cleaning up

Methods for cleaning up In dusty environments, use vacuum equipment where possible to minimize dust levels.

Reference to other sections For personal protection, see Section 8. For waste disposal, see Section 13.

7. Handling and storage

Precautions for safe handling

Usage precautions Assure proper respiratory protection if dust potential exceeds PEL/TLV.

Conditions for safe storage, including any incompatibilities

Storage precautions To ensure optimum product performance; when packaging is removed or opened; products should be stored inside or covered to protect them from ingress of rain water or snow. Storage arrangements should ensure stability of stacked products and use on a first in first out basis (FIFO) is recommended.

Specific end uses(s)

Specific end use(s) Thermal insulation for use in industrial applications OEM DAP product.

Rock Mineral Wool Insulation Material (Needled Felt)

8. Exposure Controls/personal protection

Control parameters

Occupational exposure limits

Vitreous silicate fibers produced under process conditions

Long-term exposure limit (8-hour TWA): ACGIH 1 f/cc Rock wool fibers

Long-term exposure limit (8-hour TWA): NIOSH 5 mg/m³ Mineral wool fiber, total particulate

Long-term exposure limit (8-hour TWA): OSHA 5 mg/m³ Particulates not otherwise regulated (PNOR), respirable fraction

Long-term exposure limit (8-hour TWA): OSHA 15 mg/m³ Particulates not otherwise regulated (PNOR), total dust

ACGIH = American Conference of Governmental Industrial Hygienists.

OSHA = Occupational Safety and Health Administration.

NIOSH = The National Institute for Occupational Safety and Health.

Ingredient comments (A3) - Fibers longer than 5 µm; diameter less than 3 µm; aspect ratio greater than 5:1 as determined by the membrane filter method at 400-450X magnification (4-mm objective) phase contrast illumination.
Biosoluble rock mineral wool fiber - See section 3.

Exposure controls

Appropriate engineering controls Maintain sufficient mechanical or natural ventilation to assure fiber concentrations remain below PEL/TLV. Use local exhaust if necessary. Power equipment should be equipped with properly designed dust collection devices.

Eye/face protection Use glasses or goggles when working with mineral wool insulation above shoulder height or in dusty environments.

Other skin and body protection Minimize direct contact with skin in order to prevent mechanical itching.

Hygiene measures After contact with the product, rinse skin in cold water to reduce potential effects of mechanical itching.

Respiratory protection In dusty environments, use suitable respiratory protection.

Thermal hazards Not relevant.

Rock Mineral Wool Insulation Material (Needled Felt)

9. Physical and Chemical Properties

Information on basic physical and chemical properties

Appearance	Solid. Mat.
Color	Grey.
Odor	Not relevant.
Odor threshold	No data available.
pH	Not relevant.
Melting point	> 1832°F
Initial boiling point and range	Not relevant.
Flash point	Not relevant.
Evaporation rate	Not relevant.
Flammability (solid, gas)	Not relevant.
Upper/lower flammability or explosive limits	Not relevant.
Vapor pressure	Not relevant.
Vapor density	Not relevant.
Relative density	Various from 20 - 200 kg/m ³
Solubility(ies)	Generally chemically inert and insoluble in water.
Partition coefficient	Not relevant.
Auto-ignition temperature	Not relevant.
Decomposition Temperature	Not relevant.
Viscosity	Not relevant.
Explosive properties	Not relevant.
Oxidizing properties	Not relevant.
Nominal diameter of fibers.	3 - 7 μm
Length weight geometric mean diameter less 2 standard errors	≈ 6 μm
Orientation of fibers	Random

10. Stability and reactivity

Reactivity	None.
Stability	Stable in normal conditions of use.
Possibility of hazardous reactions	None in normal conditions of use.
Conditions to avoid	None.

Rock Mineral Wool Insulation Material (Needled Felt)

Materials to avoid	None.
Hazardous decomposition products	None in normal conditions of use.

11. Toxicological information

Information on toxicological effects

Acute toxicity - oral

Notes (oral LD₅₀) No data were identified for the product as a whole. Data are for constituents: Biosoluble Rock Mineral Wool - Not applicable.

Acute toxicity - dermal

Notes (dermal LD₅₀) No data were identified for the product as a whole. Data are for constituents: Biosoluble Rock Mineral Wool - Not applicable.

Acute toxicity - inhalation

Notes (inhalation LC₅₀) No data were identified for the product as a whole. Data are for constituents: Biosoluble Rock Mineral Wool - Not applicable.

Skin corrosion/irritation

Skin corrosion/irritation May cause mechanical irritation to skin.

Serious eye damage/irritation

Serious eye damage/irritation May cause mechanical irritation to eyes.

Respiratory sensitization

Respiratory sensitization No data were identified for this product or its constituents.

Skin sensitization

Skin sensitization No data were identified for this product or its constituents.

Germ cell mutagenicity

Genotoxicity - in vitro No data were identified for this product or its constituents.

Genotoxicity - in vivo No data were identified for this product or its constituents.

Carcinogenicity

Carcinogenicity Results from a biopersistence test by intratracheal instillation has shown that fibers in this product longer than 20 µm have a weighted half-life less than 40 days, thus this product is not classified as a carcinogen. None of the components of this product are listed as a carcinogen by OSHA, IARC or NTP.

Reproductive toxicity

Reproductive toxicity - fertility No data available for this product or its constituents.

Reproductive toxicity - development No data available for this product or its constituents.

Specific target organ toxicity - single exposure

STOT - single exposure No data were identified for this product or its constituents.

Specific target organ toxicity - repeated exposure

STOT - repeated exposure No data were identified for this product or its constituents.

Aspiration hazard

Aspiration hazard Not relevant.

Rock Mineral Wool Insulation Material (Needled Felt)

Inhalation	Mechanical irritation to upper respiratory tract.
Ingestion	Non-hazardous when ingested.
Skin Contact	Mechanical irritation to skin.
Eye contact	Mechanical irritation to eyes.
Medical Symptoms	Contact with skin, eyes and upper respiratory system may cause mechanical irritation. Biosoluble rock mineral wool is classified as a nuisance dust by OSHA.

12. Ecological Information

Toxicity	This product is not ecotoxic to air, water or soil, by composition.
<u>Persistence and degradability</u>	
Persistence and degradability	Vitreous silicate fibers produced under process conditions > 99 %.
<u>Bioaccumulative potential</u>	
Bio-Accumulative Potential	Will not bioaccumulate.
Partition coefficient	Not relevant.
<u>Mobility in soil</u>	
Mobility	Not considered mobile. Less than 1% leachable organic carbon if landfilled.
<u>Other adverse effects</u>	
Other adverse effects	None known.

13. Disposal considerations

Waste treatment methods

General information	Dispose of in accordance with all applicable regulations. Empty containers should be taken to an approved waste handling site for recycling or disposal.
Disposal methods	This product is not regulated under RCRA Hazardous Waste Regulations. May be disposed in landfill. If unsure, contact the local office of the USEPA, your local public health department or the local landfill regulators.

Rock Mineral Wool Insulation Material (Needled Felt)

14. Transport information

General

The product is not covered by international regulations on the transport of dangerous goods (IMDG, IATA, DOT).

UN Number

Not applicable.

UN proper shipping name

Not applicable.

Transport hazard class(es)

No transport warning sign required.

Packing group

Not applicable.

Environmental hazards**Environmentally Hazardous Substance**

No.

Special precautions for user

Not applicable.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable.

Rock Mineral Wool Insulation Material (Needled Felt)

15. Regulatory information

Regulatory Status

This product is regulated as a nuisance dust under OSHA criteria.

In accordance with industry practice, Knauf Insulation has decided to continue to provide its customers with the appropriate information for the purpose of assuring safe handling and use of mineral wool throughout the product life.

US Federal Regulations

SARA Section 302 Extremely Hazardous Substances Tier II Threshold Planning Quantities

Not regulated.

CERCLA/Superfund, Hazardous Substances/Reportable Quantities (EPA)

Not regulated.

SARA 313 Emission Reporting

Not listed.

SARA (311/312) Hazard Categories

Not regulated.

US State Regulations

California Proposition 65 Carcinogens and Reproductive Toxins

This product is exempt from labeling requirements under this Act.

Inventories

US - TSCA

All the ingredients are listed or exempt.

Rock Mineral Wool Insulation Material (Needled Felt)

16. Other information

Abbreviations and acronyms used in the safety data sheet

CAS: Chemical Abstracts Service.
 IARC: International Agency for Research on Cancer.
 IATA: International Air Transport Association.
 IMDG: International Maritime Dangerous Goods.
 NIOSH: The National Institute for Occupational Safety and Health.
 OSHA: Occupational Safety and Health Administration.
 PBT: Persistent, Bioaccumulative and Toxic substance.
 PEL: Permissible Exposure Limit.
 SARA: Superfund Amendments and Reauthorization Act.
 TLV: Threshold Limit Value.
 TSCA: Toxic Substances Control Act.
 USEPA: United States Environmental Protection Agency.
 vPvB: Very Persistent and Very Bioaccumulative.

General information

All products manufactured by Knauf Insulation are made of non-classified fibers and are certified by EUCEB. Products meeting EUCEB certification requirements can be recognised by the EUCEB logo printed on the packaging.

Further information can be obtained from:

www.euceb.org www.knaufinsulation.com



Revision comments	1 [USA]
Revision date	2/22/2017
Revision	2.1
Supersedes date	9/28/2016
SDS No.	4667
Other information	In 2001, the International Agency for Research on Cancer (IARC) reclassified rock mineral wool fibres from Group 2B (possibly carcinogenic) to Group 3 «agent which cannot be classified as for their carcinogenicity to humans». (See Monograph Vol 81, http://monographs.iarc.fr/)

This Safety Data Sheet / Product Data Sheet does not constitute a workplace assessment. Information contained in this document represents the state of our knowledge regarding this product as of the date of issue of the document. Attention of users is drawn to possible risks taken when the product is used for other applications than the ones it has been designed for.