

**SAFETY DATA SHEET****Glass Mineral Wool with ECOSE® Technology**

According to WHMIS 2015, in compliance with the Hazardous Product Act (HPA, as amended) and the requirements of the Hazardous Product Regulations (HPR)

1. Identification**Product identifier**

Product name Glass Mineral Wool with ECOSE® Technology

Product number SI_DP_101

Synonyms; Common Names EcoBatt® (Unfaced and Faced) Building Insulation, Acoustical/IB Board, Acoustical Board Smooth, KB Blanket, Condensation Control Blanket, Guardian (Unfaced and Faced) Building Insulation, Metal Building Insulation, Metal Building Filler Insulation (*See section 2, 8, 10)

Revision date: 09/27/2016

Recommended use of the chemical and restrictions on use

Restriction on use Thermal and/or acoustic insulation for use in technical applications, industrial applications and in building construction.

Uses advised against None known.

Details of the supplier of the safety data sheet

Supplier Silvercote
25 Logue Court
Greenville SC 29615
844 232 3701
www.silvercote.com

Region: Canada

Emergency telephone number

Emergency telephone 24hrs: Chemtrec Tel: 800 424 9300

Glass Mineral Wool with ECOSE® Technology

2. Hazard identification

Classification of the substance or mixture

| | |
|--------------------------------|-------------------------|
| WHMIS Regulatory Status | Non-controlled product. |
| Physical hazards | Not Classified |
| Health hazards | Not Classified |
| Environmental hazards | Not Classified |

Label elements

| | |
|---------------------------------------|-------------------|
| Hazard statements | NC Not Classified |
| Contains | None. |
| Hazard pictogram | None. |
| Signal word | None. |
| Precautionary statements | None. |
| Supplemental label information | None. |

The following sentences and pictograms are printed on packaging:

The mechanical effect of fibers in contact with skin may cause temporary itching.



<http://www.knaufinsulation.com/comfort-and-handling>

Other hazards

| | |
|------------------------------|--|
| Physical Hazards | None. |
| Health Hazards | Mechanical irritation of the skin, eyes and upper respiratory system. |
| Environmental Hazards | None. |
| Main symptoms | Contact with skin, eyes and upper respiratory system may cause mechanical irritation. Biosoluble glass mineral wool is classified as a nuisance dust. |
| *Heat-Up Precautions | When heated to temperatures above 400°F for the first time, release of binder components and binder decomposition products can occur which, in high concentrations, may irritate eyes and the respiratory system. See section 8 & 10 |

Glass Mineral Wool with ECOSE® Technology

3. Composition/information on ingredients

Mixtures

| | |
|--|------------------|
| Biosoluble glass mineral wool | 87 - 100% |
| CAS number: — | |
| Ingredient notes:(1)(2) | |
| Classification Not Classified | |
| Thermo set, inert polymer bonding agent derived from plant starches | 0 - 13% |
| CAS number: — | |
| Classification Not Classified | |

The full text for all hazard statements is displayed in Section 16.

Ingredient notes

(1) Man made vitreous (silicate) fibers with random orientation with alkaline oxide and alkali earth oxide ($\text{Na}_2\text{O}+\text{K}_2\text{O}+\text{CaO}+\text{MgO}+\text{BaO}$) content greater than 18% by weight meeting the requirements of Note Q of regulation n° 1272/2008 and therefore not classified carcinogenicity.

(2) All Knauf Insulation products covered by this SDS are independently certified by EUCEB to be manufactured using biosoluble glass formulations.

Specific chemical identity and/or exact percent concentration is withheld as trade secret.

Glass Mineral Wool with ECOSE® Technology

4. First-aid measures

Description of first aid measures

| | |
|----------------------------|---|
| General information | Show this Safety Data Sheet to the medical professional in attendance. If symptoms occur, follow first aid measures as appropriate. |
| Notes to Physician: | No specific recommendations. |
| Inhalation | Remove from exposure. Rinse the throat and clear dust from airways. |
| Ingestion | Drink plenty of water if accidentally ingested. |
| Skin contact | If mechanical irritation occurs, remove contaminated clothing and wash skin gently with cold water and soap. |
| Eye contact | Rinse abundantly with water for at least 15 minutes. |

Most important symptoms and effects, both acute and delayed

| | |
|----------------------------|---|
| General information | Contact with skin, eyes and upper respiratory system may cause mechanical irritation. Biosoluble glass mineral wool is classified as a nuisance dust. |
|----------------------------|---|

Indication of any immediate medical attention and special treatment needed

| | |
|----------------------------|--|
| General information | If any adverse reaction or discomfort continues from any of the above exposures, seek professional medical advice. |
| Specific treatments | No specific recommendations. |

5. Fire-fighting measures

Extinguishing media

Suitable extinguishing media Water, foam, carbon dioxide (CO₂), and dry powder.

Specific hazards arising from the hazardous product

| | |
|----------------------------|--|
| General information | Products do not pose a fire hazard in use; however, some packaging materials or facings may be combustible. Products of combustion from product and packaging - carbon dioxide, carbon monoxide and some trace gases such as ammonia, nitrogen oxides and volatile organic substances. |
|----------------------------|--|

Advice for firefighters

| | |
|----------------------------|---|
| General information | In large fires in poorly ventilated areas involving packaging materials respiratory protection / breathing apparatus may be required. |
|----------------------------|---|

Glass Mineral Wool with ECOSE® Technology

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Personal precautions

Minimize direct contact with skin in order to prevent mechanical itching. In dusty environments, use suitable respiratory protection such as 3M 8210, N95 or equivalent. Use glasses or goggles when working with mineral wool insulation above shoulder height or in dusty environments. Where possible, use natural ventilation during installation in order to minimize dust levels.

After contact with the product, rinse skin in cold water to reduce potential effects of mechanical itching. Dispose of surplus product in accordance with local regulations.

Use personal protection recommended in Section 8 of the SDS.

Environmental precautions

Environmental precautions Not relevant.

Methods and material for containment and cleaning up

Methods for cleaning up In dusty environments, use vacuum equipment where possible to minimize dust levels.

Reference to other sections

Reference to other sections For personal protection, see Section 8. For waste disposal, see Section 13.

7. Handling and storage

Precautions for safe handling

Usage precautions

Assure proper respiratory protection if potential dust exposure exceeds occupational exposure limits.

Conditions for safe storage, including any incompatibilities

Storage precautions

To ensure optimum product performance; when packaging is removed or opened; products should be stored inside or covered to protect them from ingress of rain water or snow. Storage arrangements should ensure stability of stacked products and use on a first in first out basis (FIFO) is recommended.

Specific end use(s)

Specific end use(s)

Thermal and/or acoustic insulation for use in technical applications, industrial applications and in building construction.

Glass Mineral Wool with ECOSE® Technology

8. Exposure Controls/personal protection

Control parameters

Occupational exposure limits

Biosoluble glass mineral wool

Long-term exposure limit (8-hour TWA): New Brunswick (Notes: (A3), ACGIH 2015) 1 f/cc Glass wool fibers
 Long-term exposure limit (8-hour TWA): Saskatchewan 1 f/cc Glass wool fibers
 Short-term exposure limit (15-minute): Saskatchewan 3 f/cc Glass wool fibers
 Long-term exposure limit (8-hour TWA): Nunavut 1 f/cc Glass wool fibers
 Short-term exposure limit (15-minute): Nunavut 3 f/cc Glass wool fibers
 Long-term exposure limit (8-hour TWA): Newfoundland-Labrador (Note: (A3)) 1 f/cc Glass wool fibers
 Long-term exposure limit (8-hour TWA): Manitoba (Note: (A3)) 1 f/cc Glass wool fibers
 Long-term exposure limit (8-hour TWA): Nova Scotia (Note: (A3)) 1 f/cc Glass wool fibers
 Long-term exposure limit (8-hour TWA): Prince Edward Island (Note: (A3)) 1 f/cc Glass wool fibers
 Long-term exposure limit (8-hour TWA): Yukon 10 mg/m³ Mineral wool fibers, respirable
 Long-term exposure limit (8-hour TWA): NWT 1 f/cc Glass wool fibers
 Short-term exposure limit (15-minute): NWT 3 f/cc Glass wool fibers
 Long-term exposure limit (8-hour TWA): Quebec 2 f/cc Glass wool fibers
 Long-term exposure limit (8-hour TWA): Alberta 1 f/cc Glass wool fibers
 Long-term exposure limit (8-hour TWA): BC 1 f/cc Glass wool fibers
 Long-term exposure limit (8-hour TWA): Ontario (Note: Ont) 1 f/cc Glass wool fibers
 Long-term exposure limit (8-hour TWA): Alberta (Note: (3)) 10 mg/m³ Particulates not otherwise regulated (PNOR), total dust
 Long-term exposure limit (8-hour TWA): Alberta (Note: (3)) 3 mg/m³ Particulates not otherwise regulated (PNOR), respirable fraction
 Long-term exposure limit (8-hour TWA): Quebec 10 mg/m³ Particulates not otherwise regulated (PNOR), total dust

Ingredient comments

(A3) - Fibers longer than 5 µm; diameter less than 3 µm; aspect ratio greater than 5:1 as determined by the membrane filter method at 400-450X magnification (4-mm objective) phase contrast illumination.
 ACGIH Carcinogen List.
 Ont: Listed in Table 1 of Ontario Regulation 490/09.
 (3) - Based on irritation effects. Adjustment to compensate for unusual work schedules is not required.
 Biosoluble glass mineral wool - see section 3

Exposure controls

Appropriate engineering controls

Maintain sufficient mechanical or natural ventilation to assure fiber concentrations remain below occupational exposure limits. Use local exhaust if necessary. Power equipment should be equipped with properly designed dust collection devices.

Eye/face protection

Use glasses or goggles when working with mineral wool insulation above shoulder height or in dusty environments.

Other skin and body protection

Minimize direct contact with skin in order to prevent mechanical itching.

Hygiene measures

After contact with the product, rinse skin in cold water to reduce potential effects of mechanical itching.

Respiratory protection

In dusty environments, use suitable respiratory protection.

Environmental exposure controls

Not relevant.

Glass Mineral Wool with ECOSE® Technology

*** Heat-Up Precautions:** When heated to temperatures above 400°F for the first time, release of binder components and binder decomposition products can occur which, in high concentrations, may irritate eyes and the respiratory system. The duration of release is dependant upon the thickness of the insulation, binder content and the temperature applied. Adequate ventilation should be provided. In confined spaces or where ventilation is not possible, occupants should wear appropriate self-contained breathing apparatus.

9. Physical and Chemical Properties

Information on basic physical and chemical properties

| | |
|---|--|
| Appearance | Solid. Rolls. Panel. Loose fiber. |
| Colour | Brown. |
| Odour | Not relevant. |
| Odour threshold | No data available. |
| pH | Not relevant. |
| Melting point | Not relevant. |
| Initial boiling point and range | Not relevant. |
| Flash point | Not relevant. |
| Evaporation rate | Not relevant. |
| Flammability (solid, gas) | Not relevant. |
| Upper/lower flammability or explosive limits | Not relevant. |
| Vapour pressure | Not relevant. |
| Vapour density | Not relevant. |
| Relative density | 7 - 96 kg/m ³ |
| Solubility(ies) | Generally chemically inert and insoluble in water. |
| Partition coefficient | Not relevant. |
| Auto-ignition temperature | Not relevant. |
| Decomposition Temperature | Not relevant. |
| Viscosity | Not relevant. |
| Explosive properties | Not relevant. |
| Oxidising properties | Not relevant. |
| Nominal diameter of fibers. | 3 - 8 µm |
| Length weight geometric mean diameter less 2 standard errors | < 6 µm |
| Orientation of fibers | Random |

10. Stability and reactivity

| | |
|-------------------|-------|
| Reactivity | None. |
|-------------------|-------|

Glass Mineral Wool with ECOSE® Technology

| | |
|---|--|
| Stability | Binder will decompose above 400°F |
| Possibility of hazardous reactions | None. |
| Conditions to avoid | Heating above 400°F |
| Materials to avoid | Hydrofluoric acid will react with and dissolve glass. |
| Hazardous decomposition products | None in normal conditions of use. When heated to temperatures above 400°F for the first time, release of binder components and binder decomposition products can occur which, in high concentrations, may irritate eyes and the respiratory system. The duration of release is dependant upon the thickness of the insulation, binder content and the temperature applied. Adequate ventilation should be provided. In confined spaces or where ventilation is not possible, occupants should wear appropriate self-contained breathing apparatus. |

11. Toxicological information

Information on toxicological effects

Acute toxicity - oral

Notes (oral LD₅₀)

No data were identified for the product as a whole. Data are for constituents:
 Biosoluble glass mineral wool - Not applicable.
 Thermo set, inert polymer bonding agent derived from plant starches - Not applicable.

Acute toxicity - dermal

Notes (dermal LD₅₀)

No data were identified for the product as a whole. Data are for constituents:
 Biosoluble glass mineral wool - Not applicable.
 Thermo set, inert polymer bonding agent derived from plant starches - Not applicable.

Acute toxicity - inhalation

Notes (inhalation LC₅₀)

No data were identified for the product as a whole. Data are for constituents:
 Biosoluble glass mineral wool - Not applicable.
 Thermo set, inert polymer bonding agent derived from plant starches - Not applicable.

Skin corrosion/irritation

Skin corrosion/irritation

May cause mechanical irritation to skin.

Serious eye damage/irritation

Serious eye damage/irritation

May cause mechanical irritation to eyes.

Respiratory sensitization

Respiratory sensitization

No data were identified for this product or its constituents.

Skin sensitization

Skin sensitization

No data were identified for this product or its constituents.

Germ cell mutagenicity

Genotoxicity - in vitro

No data were identified for this product or its constituents.

Genotoxicity - in vivo

No data were identified for this product or its constituents.

Carcinogenicity

Carcinogenicity

Results from a biopersistence test by intratracheal instillation has shown that fibers in this product longer than 20 µm have a weighted half-life less than 40 days, thus this product is not classified as a carcinogen. None of the components of this product are listed by IARC as known or suspected carcinogens.

Reproductive toxicity

Glass Mineral Wool with ECOSE® Technology

Reproductive toxicity - fertility No data available for this product or its constituents.

Reproductive toxicity - development No data available for this product or its constituents.

Specific target organ toxicity - single exposure

STOT - single exposure No data were identified for this product or its constituents.

Specific target organ toxicity - repeated exposure

STOT - repeated exposure No data were identified for this product or its constituents.

Aspiration hazard

Aspiration hazard Not relevant.

Inhalation Mechanical irritation to upper respiratory tract.

Ingestion Non-hazardous when ingested.

Skin contact Mechanical irritation to skin.

Eye contact Mechanical irritation to eyes.

Medical symptoms Contact with skin, eyes and upper respiratory system may cause mechanical irritation. Biosoluble glass mineral wool is classified as a nuisance dust.

12. Ecological Information

Toxicity This product is not ecotoxic to air, water or soil, by composition.

Persistence and degradability

Persistence and degradability Inert inorganic product with Thermo set, inert polymer bonding agent derived from plant starches; 0 - 13%

Bioaccumulative potential

Bioaccumulative potential Will not bioaccumulate.

Partition coefficient Not relevant.

Mobility in soil

Mobility Not considered mobile. Less than 1% leachable organic carbon if landfilled.

Results of PBT and vPvB assessment

Results of PBT and vPvB assessment Not relevant.

Other adverse effects

Other adverse effects None known.

13. Disposal considerations

Waste treatment methods

General information Dispose of in accordance with all applicable regulations. Empty containers should be taken to an approved waste handling site for recycling or disposal.

Disposal methods This product is not regulated under RCRA Hazardous Waste Regulations. May be disposed in landfill. If unsure, contact your local public health department or the local landfill regulators.

14. Transport information

Glass Mineral Wool with ECOSE® Technology

| | |
|---|--|
| General | The product is not covered by international regulations on the transport of dangerous goods (IMDG, IATA, TDG). |
| <u>UN number</u> | |
| UN No. (International) | Not applicable. |
| <u>UN proper shipping name</u> | |
| Proper shipping name (International) | Not applicable. |
| <u>Transport hazard class(es)</u> | |
| Transport Labels (International) | No transport warning sign required. |
| <u>Packing group</u> | |
| Packing group (International) | Not applicable. |
| <u>Environmental hazards</u> | |
| Environmentally hazardous substance/marine pollutant | |
| No. | |
| <u>Special precautions for user</u> | |
| Not applicable. | |
| Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code | Not applicable. |

15. Regulatory information

| | |
|---|--|
| Regulatory Status | Not classified according to WHMIS In accordance with industry practice, Silvercote has decided to continue to provide its customers with the appropriate information for the purpose of assuring safe handling and use of mineral wool throughout the product life. |
| <u>Inventories</u> | |
| Canada – DSL/NDSL | All the ingredients are listed or exempt. |
| CEPA - Priority Substances List | All the ingredients are listed or exempt. |
| National Pollutant Release Inventory | All the ingredients are listed or exempt. |

Glass Mineral Wool with ECOSE® Technology

16. Other information

Abbreviations and acronyms used in the safety data sheet

CAS: Chemical Abstracts Service.
CEPA: Canadian Environmental Protection Act.
DSL: Domestic Substances List.
IARC: International Agency for Research on Cancer.
IATA: International Air Transport Association.
IMDG: International Maritime Dangerous Goods.
NDSL: Non-Domestic Substances List.
PBT: Persistent, Bioaccumulative and Toxic substance.
vPvB: Very Persistent and Very Bioaccumulative.
WHMIS: Workplace Hazardous Materials Information System.

General information

All products manufactured by Silvercote are made of non-classified fibres and are certified by EUCEB. Products meeting EUCEB certification requirements can be recognised by the EUCEB logo printed on the packaging

Further information can be obtained from:

www.euceb.org www.silvercote.com



Revision comments

New document format

Revision date

27/09/2016

Revision

2.0

SDS number

SI_DP_101

Other information

In 2001, the International Agency for Research on Cancer (IARC) reclassified glass mineral wool fibres from Group 2B (possibly carcinogenic) to Group 3 «agent which cannot be classified as for their carcinogenicity to humans». (See Monograph Vol 81, <http://monographs.iarc.fr/>)

This Safety Data Sheet / Product Data Sheet does not constitute a workplace assessment. Information contained in this document represents the state of our knowledge regarding this product as of the date of issue of the document. Attention of users is drawn to possible risks taken when the product is used for other applications than the ones it has been designed for.